




Notes:

- 1.Color:Natural;
- 2.RoHS Compliant;
- 3.Top Hole: $\varnothing 3.86 \pm 0.05 \text{mm}$;
Panel Thickness:1.57mm;
- 4.Bottom Hole: $\varnothing 3.86 \pm 0.05 \text{mm}$;
Panel Thickness:1.57mm;

Part No.	Part Name	Material	A
42279	GCBP-1S-66	PA66 UL94 V2	2.54
42280	GCBP-1S-V0	PA66 UL94 V0	
42281	GCBP-1-66	PA66 UL94 V2	2.0
42282	GCBP-1-V0	PA66 UL94 V0	
40419	GCBP-2-66	PA66 UL94 V2	3.2
40420	GCBP-2-V0	PA66 UL94 V0	
42283	GCBP-4M-66	PA66 UL94 V2	4.0
42284	GCBP-4M-V0	PA66 UL94 V0	
40421	GCBP-3-66	PA66 UL94 V2	4.8
40422	GCBP-3-V0	PA66 UL94 V0	
40423	GCBP-4-66	PA66 UL94 V2	6.4
40424	GCBP-4-V0	PA66 UL94 V0	
40425	GCBP-5-66	PA66 UL94 V2	7.9
40426	GCBP-5-V0	PA66 UL94 V0	
40427	GCBP-6-66	PA66 UL94 V2	9.5
40428	GCBP-6-V0	PA66 UL94 V0	
40429	GCBP-7-66	PA66 UL94 V2	11.1
40430	GCBP-7-V0	PA66 UL94 V0	
40431	GCBP-8-66	PA66 UL94 V2	12.7
40432	GCBP-8-V0	PA66 UL94 V0	
40433	GCBP-9-66	PA66 UL94 V2	14.3
40434	GCBP-9-V0	PA66 UL94 V0	
40435	GCBP-10-66	PA66 UL94 V2	15.9
40436	GCBP-10-V0	PA66 UL94 V0	
40437	GCBP-11-66	PA66 UL94 V2	17.5
40438	GCBP-11-V0	PA66 UL94 V0	
40439	GCBP-12-66	PA66 UL94 V2	19.1
40440	GCBP-12-V0	PA66 UL94 V0	
40441	GCBP-13-66	PA66 UL94 V2	20.6
40442	GCBP-13-V0	PA66 UL94 V0	
40443	GCBP-14-66	PA66 UL94 V2	22.2
40444	GCBP-14-V0	PA66 UL94 V0	
40446	GCBP-16-66	PA66 UL94 V2	25.4
40447	GCBP-16-V0	PA66 UL94 V0	
40448	GCBP-18-66	PA66 UL94 V2	28.6
40449	GCBP-18-V0	PA66 UL94 V0	
40450	GCBP-20-66	PA66 UL94 V2	31.7
40451	GCBP-20-V0	PA66 UL94 V0	
40453	GCBP-22-66	PA66 UL94 V2	34.9
40454	GCBP-22-V0	PA66 UL94 V0	
40455	GCBP-24-66	PA66 UL94 V2	38.1
40456	GCBP-24-V0	PA66 UL94 V0	

Gecko International Co.

DATE

2016-4-17

DIMENSION

TOLERANCE

TITLE

MINI SUPPORT POST

SCALE

FIT

$L \leq 4$

± 0.10

PART NAME

GCBP

MOLD NO.

S0318-20

DRAW

JF

UNIT

MM

$4 < L \leq 15$

± 0.20

PART NO.

SEE TABLE

MATERIAL

SEE TABLE

DESIGN

JF

VERSION

A0

$15 < L \leq 50$

± 0.30

DWG NO.

E4028


COLOR

SEE NOTES

APPROVAL

FDL

VIEW



$50 < L \leq 100$

± 0.40